



Press Release

December 2010

McCormick T-*Max* and better spec loaders at LAMMA 2011



- T100-*Max* bridges spec and price gap between C-*Max* and CX models
- Perkins four-cylinder delivers 92hp; 36x12 gearbox, three-speed powershift
- LiftMaster loader specification improved for easier materials handling

Farmers viewing the McCormick exhibits on the AgriArgo UK stand at LAMMA 2011 will have their first chance to 'check the spec' on the latest newcomer to the range – the 92hp T100-*Max*.

They will also see the latest LiftMaster loader models with additional standard features designed to make them easier to use.

The **McCormick T100-*Max*** is a fourth option in the McCormick range for farmers wanting a 92hp all-purpose tractor for loader and general duties on mixed and arable farms, livestock and field vegetable units.

With a new transmission and back axle assembly installed, the T100-*Max* scores over the simpler C100-*Max* and CX100 LP Synchro in having more transmission speeds, a power shuttle, hydraulic control of the pto and front axle drive engagement.

It also has a telescopic pick-up hitch; and while manual control of the implement lift matches the system used on the C100-*Max*, draft sensing is through the lower links.

"The T100-*Max* comes with a 36x12 speed transmission with power shuttle and three-speed powershift," notes McCormick product specialist, Paul Wade. "It joins the existing C-*Max* and CX models to give farmers a four-way choice of 92hp tractors in the McCormick range to meet their particular requirements."

The **McCormick LiftMaster** loaders at LAMMA 2011 will have new features to help make them more productive and easier to use. There is a big choice of models, capacities and lift heights to suit all tractors and applications.

A new main oil distribution valve provides a 'float' feature for the first time. This is useful when running a fork or bucket along a hard surface because it allows the loader arms to rise and fall and the attachment to follow any dips and bumps without digging in.

An attachment level indicator rod is now included as standard to help operators set a fork or bucket at the correct angle for digging into a stockpile of manure, silage or grain.

Upright 'bull bars' now protect the front of the tractor from accidental damage when filling a high-sided spreader or trailer. As with the mounting frame itself, which extends to the back axle to spread loads and stresses, the bull bars are designed to avoid getting in the way of any service items on the tractor.

Ends



McCormick T100-Max 01.jpg

With a new New McCormick T100-Max represents another price-spec package for buyers wanting a well-specced, low profile 92hp tractor.



McCormick T100-Max 02.jpg

New T100-Max represents another price-spec package for buyers wanting a well-specced, low profile 92hp tractor from the McCormick range.



McCormick CX110 XtraShift+LiftMaster I-30H loader 03A.jpg

Added refinements to McCormick LiftMaster loaders like this 1500kg/3.87m I-30H model with hydraulic self-levelling include float and a bucket level gauge as standard. New bull bars protect the front of the tractor.



For further information please contact:

McCormick – AgriArgo UK Ltd

Tel: 01302 757550

Fax: 01302 757585

Email: info@agriargouk.com

Website: www.agriargouk.co.uk

Website: www.argotracors.com



For press releases and images on McCormick products, people, dealers:

Peter Hill – Farmpress / Tel: 01491 824355

Email: AgriArgoUK@aol.com